- (k) Battery handling equipment which could contact battery terminals or cell connectors shall be insulated or otherwise protected.
- (1) Metallic objects shall not be placed on uncovered batteries.
- (m) When batteries are being charged, the vent caps shall be in place.
- (n) Chargers shall be turned off when leads are being connected or disconnected.
- (o) Installed batteries shall be secured to avoid physical or electrical

contact with compartment walls or components.

[48 FR 30909, July 5, 1983, as amended at 62 FR 40202, July 25, 1997]

§ 1917.158 Prohibited operations.

- (a) Spray painting and abrasive blasting operations shall not be conducted in the vicinity of cargo handling operations.
- (b) Welding and burning operations shall not be conducted in the vicinity of cargo handling operations unless such hot work is part of the cargo operation.

APPENDIX I TO PART 1917—SPECIAL CARGO GEAR AND CONTAINER SPREADER TEST REQUIREMENTS (MANDATORY) [SEE § 1917.50(c)(5)]

Type gear	Test requirement	Tested by	Proof test				
A. All Special Cargo Handling Gear Purchased or Manufactured on or After January 21, 1998							
1. Safe Working Load—greater than 5 short tons (10,000 lbs./4.5 metric tons).	Prior to initial use	OSHA accredited agency only.	Up to 20 short tons.	125% SWL			
,.	Prior to reuse after structural damage repair		From 20 to 50 short tons	5 short tons in excess of SWI			
	Every four years after initial proof load test	OSHA accredited agency or designated person (40)(1) 125% SWL	Over 50 short tons	110% SWL			
2. Safe Working Load—5 short tons or less.	Prior to initial use Prior to reuse after structural damage repair	OSHA accredited agency or designated person	125% SWL				
3. Intermodal container spreaders not part of vessel's cargo han- dling gear.	Prior to initial use						
dirig godi.	Prior to reuse after structural	OSHA accredited agency					
	damage repair Every four years after initial proof load test.	only OSHA accredited agency or designated person.	125% SWL				
	B. All Special Cargo Hand	ling Gear in Use Prior to Janu	uary 21, 1998				
1. Any Safe Working Load.	Every four years starting on January 21, 1998.	OSHA accredited agency or designated person.	Up to 20 short tons.				
	Prior to initial use or prior to reuse after structural damage repair	OSHA accredited agency	From 20 to 50 short tons Over 50 short tons	5 short tons in excess of SWL 110% SWL			

Pt. 1918

2. Intermodal container spreaders	Every four years starting on January 21, 1998	OSHA accredited agency or designated person		
not part of ship's gear.				
	Prior to initial use or prior to reuse after structural damage repair	OSHA accredited agency	125%	SWL

[65 FR 40943, June 30, 2000]

PART 1918—SAFETY AND HEALTH REGULATIONS FOR LONGSHORING

Subpart A—General Provisions

Sec.

1918.1 Scope and application.

1918.2 Definitions.

1918.3 Incorporation by reference

1918.4 OMB control numbers under the Paperwork Reduction Act.

Subpart B—Gear Certification

1918.11 Gear certification (See also §§ 1918.2, definition of "Vessel's cargo handling gear" and 1918.51).

Subpart C—Gangways and Other Means of Access

1918.21 General requirements.

1918.22 Gangways.

1918.23 Jacob's ladders.

1918.24 Fixed and portable ladders.

1918.25 Bridge plates and ramps (See also $\S1918.86$).

1918.26 Access to barges and river towboats.

Subpart D—Working Surfaces

1918.31 Hatch coverings.

1918.32 Stowed cargo and temporary landing surfaces.

1918.33 Deck loads.

1918.34 Other decks.

1918.35 Open hatches.

1918.36 Weather deck rails.

1918.37 Barges.

Subpart E—Opening and Closing Hatches

1918.41 Coaming clearances.

1918.42 Hatch beam and pontoon bridles.

1918.43 Handling hatch beams and covers.

Subpart F—Vessel's Cargo Handling Gear

1918.51 General requirements (See also $\S1918.11$ and appendix III of this part).

 $1918.52 \quad {\bf Specific\ requirements.}$

1918.53 Cargo winches.

1918.54 Rigging gear.

1918.55 Cranes (See also §1918.11).

Subpart G—Cargo Handling Gear and Equipment Other Than Ship's Gear

1918.61 General (See also appendix IV of this part).

1918.62 Miscellaneous auxiliary gear.

1918.63 Chutes, gravity conveyors and rollers.

1918.64 Powered conveyors.

1918.65 Mechanically-powered vehicles used aboard vessels.

1918.66 Cranes and derricks other than vessel's gear.

1918.67 Notifying ship's officers before using certain equipment.

1918.68 Grounding.

1918.69 Tools.

1918.70–1918.80 [Reserved]

Subpart H—Handling Cargo

1918.81 Slinging.

1918.82 Building drafts.

1918.83 Stowed cargo; tiering and breaking down.

1918.84 Bulling cargo.

1918.85 Containerized cargo operations.

1918.86 Roll-on roll-off (Ro-Ro) operations (see also §1918.2, Ro-Ro operations, and §1918.25).

1918.87 Ship's cargo elevators.

1918.88 Log operations.

1918.89 Handling hazardous cargo (See also §1918.2 and §1918.99).

Subpart I—General Working Conditions

1918.90 Hazard communication.

1918.91 Housekeeping.

1918.92 Illumination.

1918.93 Hazardous atmospheres and substances (See also §1918.2).

1918.94 Ventilation and atmospheric conditions (See also §1918.2, definitions of Hazardous cargo, materials, substance or atmosphere and Ro-Ro operations).

1918.95 Sanitation.

1918.96 Maintenance and repair work in the vicinity of longshoring operations.

1918.97 First aid and lifesaving facilities. (See appendix V of this part).

1918.98 Qualifications of machinery operators and supervisory training.

1918.99 Retention of DOT markings, placards and labels.

1918.100 Emergency action plans.